

Three Phase Hybrid Inverter

SUN-25/29.9/30K-SG02HP3-EU-AM3



Deye
TPFP

Stock Code: 605117.SH

- ☐ 100% unbalanced output, each phase
- ☒ AC couple to retrofit existing solar system
- ☐ Max. 10 pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel
- ☐ Max. charging/discharging current of 75A
- ☐ High voltage battery, higher efficiency
- ☐ 6 time periods for battery charging/discharging
- ☒ Support storing energy from diesel generator

تهران، پارک فناوری پردیس، خیابان نوآوری ۱۲، پلاک ۱۲۴
کدپستی: ۱۶۵۴۱۲۰۷۸۰ | ۱۲۲ - ۰۲۱۷۶۲۵۰۱۱۴ | ۰۹۱۲۰۵۰۶۷۵۰ (فروش)

TPFP
tpfpco.com

Model	SUN-25K-SG02HP3 -EU-AM3		SUN-29.9K-SG02HP3 -EU-AM3	SUN-30K-SG02HP3 -EU-AM3
Battery Input Data				
Battery Type	Lithium-ion			
Battery Voltage Range (V)	160-700			
Max. Charging Current (A)	75			
Max. Discharging Current (A)	75			
Charging Strategy for Li-ion Battery	Self-adaption to BMS			
Number of Battery Input	1			
PV String Input Data				
Max. PV Access Power (W)	50000	59800	60000	
Max. PV Input Power (W)	40000	47840	48000	
Max. PV Input Voltage (V)	1000			
Start-up Voltage (V)	180			
MPPT Voltage Range (V)	150-850			
Rated PV Input Voltage (V)	600			
Max. Operating PV Input Current (A)	36+36+36			
Max. Input Short-Circuit Current (A)	54+54+54			
No. of MPP Trackers/No. of Strings MPP Tracker	3/2+2+2			
AC Input/Output Data				
Rated AC Input/Output Active Power (W)	25000	29900	30000	
Max. AC Input/Output Apparent Power (VA)	27500	29900	33000	
Rated AC Input/Output Current (A)	37.9/36.3	45.4/43.4	45.5/43.5	
Max. AC Input/Output Current (A)	41.7/39.9	45.4/43.4	50/47.9	
Max. Continuous AC Passthrough (grid to load) (A)	80			
Peak Power (off-grid) (W)	1.5 times of rated power, 10s			
Power Factor Adjustment Range	0.8 leading to 0.8 lagging			
Rated Input/Output Voltage/Range (V)	220/380V, 230/400V 0.85Un-1.1Un			
Rated Input/Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65			
Grid Connection Form	3L+N+PE			
Total Current Harmonic Distortion THDi	<3% (of nominal power)			
DC Injection Current	<0.5% In			
Efficiency				
Max. Efficiency	98.50%			
Euro Efficiency	98.0%			
MPPT Efficiency	>99%			
Equipment Protecton				
Integrated	DC Reverse Polarity Protection, AC Output Overcurrent Protection, Thermal Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, DC Component Monitoring, Arc Fault Circuit Interrupter (optional), Anti-islanding Protection, DC Switch, Insulation Impedance Detection, Residual Current Detection			
Surge Protection Level	TYPE II(DC), TYPE II(AC)			
Interface				
LCD/LED Display	LCD+LED			
Communication Interface	RS485/RS232/CAN			
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN(optional)			
Operating Temperature Range (	-40 to +60			
	0-100%			
	3000m			
	≤55			
	IP 65			
	Non-Isolated			
	OVC II(DC), OVC III(AC)			
	448x688x 270(Excluding Connectors and Brackets)			
Weight (kg)	46			
Type of Cooling	Intelligent air cooling			
Warranty	5 Years/10 Years the Warranty Period Depends the Final Installation Site of Inverter, More Info Please Refer to Warranty Policy			
Grid Regulation	IEC 61727,IEC 62116,CEI 0-21,EN 50549			
Safety / EMC Standard	IEC/EN 61000-6-1/2/3/4. IEC/EN 62109-1. IEC/EN 62109-2			